




BEARING PRECISION AXLE CORP.



60 mm x 130 mm x 46 mm SKF NU 2312 ECM thrust ball bearings

Bearing No. NU 2312 ECM

NU 2312 ECM Bearing 2D drawings and 3D CAD models

Size	130x60x46 mm
Bore Diameter	130 mm
Outer Diameter	60 mm
Width	46 mm
d	60 mm
D	130 mm
B	46 mm
D ₁	108.5 mm
F	77 mm
r _{1,2} - min.	2.1 mm
r _{3,4} - min.	2.1 mm
s	3.6 mm
d _a - min.	72 mm
d _a - max.	74 mm
d _b - min.	79 mm
D _a - max.	118.1 mm
r _a - max.	2 mm
r _b - max.	2 mm
Basic dynamic load rating - C	260 kN
Basic static load rating - C ₀	265 kN
Fatigue load limit - P _u	34.5 kN
Reference speed	5600 r/min
Limiting speed	6700 r/min
Calculation factor - k _r	0.25



BEARING PRECISION AXLE CORP.

Category	Cylindrical Roller Bearings
Inventory	0.0
Manufacturer Name	SKF
Minimum Buy Quantity	N/A
Weight / Kilogram	3.177
EAN	7316570174175
Product Group	B04144
Bore Profile	Straight
Cage Material	Brass
Precision Class	RBEC 1 ISO P0
Number of Rows of Rollers	Single Row
Separable	Inner Ring - Both Sides
Rolling Element	Cylindrical Roller Bearing
Profile	Complete with Outer and Inner Ring
Snap Ring	No
Internal Clearance	C0-Medium
Retainer	Yes
Relubricatable	Yes
Inch - Metric	Metric
Other Features	High Capacity Plain Inner Ring 2 Rib Outer Ring Cage on Outer Ring ID
Long Description	60MM Bore; Straight Bore Profile; 130MM Outside Diameter; 46MM Width; Brass Cage Material; RBEC 1 ISO P0; Single Row; Inner Ring - Both Sides Separable; No Snap Ring; Relubricatable; C0-Medium Inte
Category	Cylindrical Roller Bearing
UNSPSC	31171547
Harmonized Tariff Code	8482.50.00.00
Noun	Bearing



BEARING PRECISION AXLE CORP.

Manufacturer URL	http://www.skf.com
Manufacturer Item Number	NU 2312 ECM
Weight / LBS	6.998
Bore	2.362 Inch 60 Millimeter
Width	1.811 Inch 46 Millimeter
Outside Diameter	5.118 Inch 130 Millimeter
bore diameter:	60 mm
static load capacity:	265 kN
outside diameter:	130 mm
precision rating:	Not Rated
overall width:	46 mm
maximum rpm:	6700 RPM
flanges:	(2) Outer Ring
bearing material:	Steel
bore type:	Straight
cage material:	Brass
number of rows:	1
finish/coating:	Uncoated
internal clearance:	C0
closure type:	Open
ring separation:	Separable Ring
outer ring width:	46 mm
operating temperature range:	Maximum of +300 ° F
fillet radius:	2 mm
dynamic load capacity:	260 kN
series:	NU23
D_1	108.5 mm
$r_{1,2}$ min.	2.1 mm
$r_{3,4}$ min.	2.1 mm
s max.	3.6 mm
d_a min.	72 mm



BEARING PRECISION AXLE CORP.

d_a max.	74 mm
d_b min.	79 mm
D_a max.	118.1 mm
r_a max.	2 mm
r_b max.	2 mm
Basic dynamic load rating C	260 kN
Basic static load rating C_0	265 kN
Fatigue load limit P_u	34.5 kN
Calculation factor k_r	0.25
Limiting value e	0.3
Axial load factor Y	0.4
Mass bearing	3.12 kg